

## **TECHNICAL RIDER**

	s Technical Rider is hereby attached to the Contract for the performance date of, ween the parties named herein.			
1.	Purchaser:			
	Address			
	City, State, Zip			
	Phone Fax E-mail			
2.	Artist Victoria & Zeta Five			
	Artist Advance Contact			
	Address Advance Contact			
	Phone Fax E-mail			
3.	Place of Engagement			
	Address			
	City, State, Zip			
4.	Day of Show Phone  Type of Performance (i.e., concert, workshop, festival, etc.)			
5.	Number of Sets and Length			
6.	Audience Capacity			
7.	Load-in to be determined by			
	Hall will be available for load-in and setup by technical crew at			
	and for Artist load-in at			
8.	Sound Check			
	Hall will be available for Artist sound check (date) (time). All sound reinforcement systems shall be in place, in good working order with room EQ'd, prior to Artist's arrival for sound check. Artist requires a (hours(s)) setup and sound check period. Artist shall complete setup and sound check (hour(s)) prior to performance time provided that all equipment is in good working order and hall was accessible at the times indicated above. Purchaser shall not permit the doors to open to audience until all technical and sound checks have been completed to Artist's satisfaction. Purchaser, technical crew and Artist agree to make every effort to start the performance on time. Purchaser shall pay Artist penalty for starting the performance later than minutes past the contracted start time due to the fault of the Purchaser. Any additional expenses, like union overtime charges shall be the sole responsibility of the Purchaser when the expense occurs due to a late start.			

TECHNICAL RIDER Page 2

Ноги	se Console	
nou:	Input channels	
	1-Band EQ on each channel	
,	Acceptable brands	
	se Rack (Outboard Gear) Digital Reverb	
_	Digital Delay	
	Outboard Compressors	
-	1/3-Octave Equalizer for stereo setup	
-	CD player Cassette Player/Recorder set up for record and playback	
	se Speakers Stereo 3- or 4-way system shall adequately provide coverage for venue	
	Artist prefers system to be flown whenever possible	
	Speakers should be angled for adequate balcony coverage when not flown	
Hou	se Mix Position	
	Stage Right Center or Stage Left Center	
I	Not more than feet from the stage	
Stag	Not more than feet from the stage Jnacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console	
Stag	Not more than feet from the stage Jnacceptable Mix positions: behind walls, under balconies, in balcony e Monitor System	
Stag	Not more than feet from the stage Jnacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console I-Band Sweepable EQ on each input  Preferred brands	
Stag	Not more than feet from the stage Jnacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console I-Band Sweepable EQ on each input Preferred brands 1/3-Octave EQ's	
Stag	Not more than feet from the stage Jnacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console H-Band Sweepable EQ on each input Preferred brands 1/3-Octave EQ's Reverb Unit	
Stag	Not more than feet from the stage Jnacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console I-Band Sweepable EQ on each input Preferred brands 1/3-Octave EQ's	
Stag	Not more than feet from the stage Jnacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console 4-Band Sweepable EQ on each input Preferred brands 1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console H-Band Sweepable EQ on each input Preferred brands  1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console H-Band Sweepable EQ on each input Preferred brands  1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer  Itor Mix Position	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console H-Band Sweepable EQ on each input Preferred brands  1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer  Itor Mix Position On Stage (left or right): Engineer must have full view of stage with no obstructions.	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console 4-Band Sweepable EQ on each input Preferred brands  1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer  Itor Mix Position On Stage (left or right): Engineer must have full view of stage with no obstructions.  Stage Equipment	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console H-Band Sweepable EQ on each input  Preferred brands  1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer  Itor Mix Position On Stage (left or right): Engineer must have full view of stage with no obstructions.  Stage Equipment Microphones Microphones Boom Stands	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console H-Band Sweepable EQ on each input Preferred brands  1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer  for Mix Position On Stage (left or right): Engineer must have full view of stage with no obstructions.  Stage Equipment Microphones Boom Stands Straight Stands	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console H-Band Sweepable EQ on each input  oreferred brands  1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer  itor Mix Position On Stage (left or right): Engineer must have full view of stage with no obstructions.  Stage Equipment Microphones Boom Stands Straight Stands Straight Stands Electric Quad Boxes	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console I-Band Sweepable EQ on each input  Preferred brands  1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer  Itor Mix Position On Stage (left or right): Engineer must have full view of stage with no obstructions.  Stage Equipment Microphones Boom Stands Straight Stands Electric Quad Boxes Active Direct Boxes	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console I-Band Sweepable EQ on each input Preferred brands 1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer  for Mix Position On Stage (left or right): Engineer must have full view of stage with no obstructions.  Stage Equipment Microphones Boom Stands Straight Stands Electric Quad Boxes Active Direct Boxes Piano (specify)	
Stag	Not more than feet from the stage Unacceptable Mix positions: behind walls, under balconies, in balcony  e Monitor System Channel console I-Band Sweepable EQ on each input  Preferred brands  1/3-Octave EQ's Reverb Unit Identical Monitor Wedges; each wedge should contain woofers plus one horn Separate Monitor Mixes  I Monitor Mix Engineer  Itor Mix Position On Stage (left or right): Engineer must have full view of stage with no obstructions.  Stage Equipment Microphones Boom Stands Straight Stands Electric Quad Boxes Active Direct Boxes	

**TECHNICAL RIDER** Page 3 All technical guestions regarding equipment and Artist's requirements must be directed to Artist Representative (Name) (Phone) 10. Personnel Purchaser agrees to hire a professional sound company including sound engineers trained to set up and run the technical equipment specified in this Technical Rider. If technical personnel are provided other than from a professional sound company, Artist must be notified. The name and contact numbers are: 11. Stage Plot Artist will provide Purchaser with the following when the completed contract (wc) is returned or during sound check: A current stage plot and line input chart (wc) \_\_\_\_ A set list (sc) \_\_\_\_ A list of soloing musicians (sc) Special information regarding backup tapes, effects, sampling and computer-generated sounds (sc) 12. Lighting Purchaser shall provide a professional lighting system with adequate personnel to operate the house system and any follow spots. When Artist provides a lighting design and plot, Purchaser's designated lighting technician shall contact Artist or Artist's representative at least two (2) weeks prior to engagement. Purchaser's lighting technician contact Phone Lighting requirements when a light plot is not provided should be simple and enhance the performance. Lighting should frame artists directly. Avoid light spills into the audience or unnecessarily lighting unused portions of the stage. Operator must be present during sound check to position and final-focus lights: Follow Spots with Operator Leko's placed and focused one on each player position to highlight solos Par64's for front, rear and side fills to provide general wash with colored gels Acceptable Flesh Tone Gels: pale lavender, pale pinks and light reds Acceptable Mood Gels: reds, blues, purples, ambers **Dimmer Board and Operator** Artist shall instruct operator regarding specific light cues or mood changes during sound check. Unless otherwise instructed, lighting and color changes should be kept to a minimum and compliment the performance. 13. Purchaser is responsible for providing copies of this Technical Rider to the appropriate personnel not less than two weeks prior to the engagement. Victoria L. Hammill, Solo Artist / Musician Artist's Name and Title Purchaser's Name and Title

Date

Authorized Signature

Date

**Authorized Signature**